



MODEL
T510K

KEL-BERG 3-AXLE 30T DRAWBAR
TIPPING TRAILER 25 M³

SPECIFICATION FOR T510K

KEL-BERG 3-AXLE 30T DRAWBAR TIPPING TRAILER 25 M³

WEIGHTS & MEASURES:

Total length	12,260 – 14,460 mm
Drawbar length	3,200 – 5,400 mm
Front overhang	900 mm
Rear overhang	1,700 mm
Coupling height	650 mm
Width	2,550 mm
Axle distance	4,650 mm / 1,810 mm

BODY DIMENSIONS:

Length inside	7,500 mm
Internal width	2,440 mm
Height inside	1,350 mm
KBM	25
Tipping angle	46 degrees

Speed:	90 km/h
Front axle pressure	10,000 kg
Rear axle load	20,000 kg
Total weight	30,000 kg
Service weight	5,950 kg

CHASSIS:

Made with heavy duty main frame, welded steel construction with Trako pulls.



SPECIFICATION FOR T510K

KEL-BERG 3-AXLE 30T DRAWBAR TIPPING TRAILER 25 M³

TIPPING BODY:

Aluminium
About 25 KBM
7mm bottom
5mm sides
Tipping cylinder Penta - MAX 170 Bar

AXLES:

1 x 10ton BPW axles with front disc brakes
2 x 10ton BPW axles with rear disc brakes
Air suspension with level valve manoeuvrable front and rear.
With ABS, EBS
3rd axle liftable, manoeuvrable from cab (Pin 10)

WHEELS:

8 pcs 385/65R22.5 mounted on steel rim M+S

BRAKES:

2-circuit compressed air system with EBS and ABS,
Spring brake bells for parking brake
1 pc duomatic red/yellow

ELECTRICAL SYSTEM:

24 Volts according to current regulations
2 x 3 multi-chamber rear LED lights
4 LED work lights



ELECTRICAL CONNECTORS:

1 x 14-pin plug for lighting

PAINTING:

Chassis colour: Optional

Tipping box colour: Optional

OTHER:

Rear reflective signs (ECE70)

Red/white contour markings on sides and rear

Fenders with anti-spray

2 pcs weight clocks

1 large Kelberg rear mudguard.

Plastic on rear underrun

Spring on tow bar

Plastic in bottom and sides