



**MODEL**  
**T350V**

**KEL-BERG 3-AXLE TIPPING**  
**TRAILER 54 KBM**

# SPECIFICATION FOR T350V

# KEL-BERG 3-AXLE TIPPING TRAILER 54 M<sup>3</sup>

## WEIGHTS & MEASURES:

Overall length	10,940 mm
Front overhang	1,055 mm
Coupling height	1,150 mm
King-pin - support leg:	2,700 mm
Width	2,529 mm
Load height	3,500 mm
King-pin - 2nd axle	8,000 mm
Centre distance	1,310 / 1,310 mm

## TRAILER DIMENSIONS:

Internal length	10,480 mm
Internal width	2,440 mm
Height inside	2,100 mm
Cubic capacity	54
Tipping angle	46 degrees

Speed	90 km/h
King-pin pressure	18,000 kg
Rear axle pressure	27,000 kg
Total weight	45,000 kg
Service weight	8,490 kg

## CHASSIS:

Made of heavy duty main frame, welded steel construction.



# SPECIFICATION FOR T350V

## KEL-BERG 3-AXLE TIPPING TRAILER 54 M<sup>3</sup>

### BODY:

7mm aluminium base.  
40mm aluminium sides, with 2.5mm strength.  
Rear hatch in the centre  
3 pcs Fold down left side 600mm

### AXLES:

3 x 9ton SAF axles with disc brakes  
1st axle liftable, drive automatic  
Air suspension with level valve manoeuvrable...  
With ABS, EBS

### WHEELS:

6pcs 385/65R22,5 mounted on Aluminium wheels M+S

### BRAKING:

2-circuit compressed air system with EBS and ABS,  
Spring brake bells for the parking brake  
1 pc Red + Yellow Air

### ELECTRICAL SYSTEM:

24 Volt according to current regulations  
2 x multi-chamber rear lights  
Diode type side/position lights  
2 x Halogen rear lamps



# SPECIFICATION FOR T350V

## KEL-BERG 3-AXLE TIPPING TRAILER 54 M<sup>3</sup>

### ELECTRICAL CONNECTORS:

2 x 7-pin plug for lighting

1 x ABS connector

### PAINTING:

3 coats of base paint with zinc primer

2 component surface coating

Colour:

Tippbalja:

Chapel:

### OTHER:

Red reflective signs (ECE70) at the rear

White reflector (ECE104) contour marking sides and rear

Footbridge

Fenders with anti-spray

2 working lights at the bumpers

2 working lights at the rear

Hansel & Gretel at left side

Manual Chapel - Silver

### OPTION ADDITIONAL:

Plastic bottom & sides

Tip valve with remote control – 3.600 mm hoses

