

**KEL-BERG**<sup>®</sup>  
TRAILERS SVERIGE AB

**LASTAS**

**HOVEDINDGANG**

TEL: +46 070-536 3939  
WEB: [www.kelberg.se](http://www.kelberg.se)

**Udlevering**

PORT  
**4**

**KEL-BERG**

**MODEL**  
**T850K**

**KEL-BERG 3-AXLE DRAWBAR**  
**DUMP TRAILER**



# SPECIFICATION FOR T850K

# KEL-BERG 3-AXLE DRAWBAR DUMP TRAILER

## WEIGHTS & MEASURES:

|                  |                  |
|------------------|------------------|
| Total length     | 9,500 mm         |
| Length of bucket | 5,100 mm         |
| Drawbar length   | 3,905 mm         |
| Rear overhang    | 1,022 mm         |
| Coupling height  | 650 mm           |
| Width            | 2,550 mm         |
| Centre distance  | 1,310 / 1,310 mm |
| Volume approx.   | 15 KBM           |

|                |           |
|----------------|-----------|
| Speed          | 90 km/h   |
| Axle pressure  | 27,000 kg |
| Total weight   | 27,000 kg |
| Service weight | 6,900 kg  |

## CHASSIS:

Made of heavy duty main frame, welded steel construction.

## BODY:

|                                    |      |
|------------------------------------|------|
| Constructed from Hardox 450 steel. |      |
| Floor thickness                    | 8 mm |
| Side wall thickness                | 6 mm |



# SPECIFICATION FOR T850K

# KEL-BERG 3-AXLE DRAWBAR DUMP TRAILER

## AXLES:

3 x 9ton SAF axles with disc brakes  
1.a + 3.de axle liftable STIFT 10 + 11  
Air suspension with leveling valve manoeuvre length  
With ABS, EBS

## WHEELS:

6 pcs 385/65R22.5 mounted on steel rim with tyres - M+S tyres

## BRAKING:

2-circuit compressed air system with EBS and ABS,  
Spring brake bells for parking brake  
1 pc duomatic red/yellow

## ELECTRICAL SYSTEM:

24 Volts according to current regulations  
2 x multi-chamber rear lights  
Diode type side/position lights  
2 x rear LED reversing lights

## ELECTRICAL CONNECTORS:

1 x 14-pin connector for lighting



# SPECIFICATION FOR T850K

# KEL-BERG 3-AXLE DRAWBAR DUMP TRAILER

## PAINTING:

3 coats of base paint with zinc primer

2 component surface coating

Colour:

Balja Colour.Ral:

## OTHER:

Red/white reflective signs (ECE70) at the rear

Yellow reflective (ECE104) side and rear contour markings

Fenders with anti-spray

Hinged hatch - Aluminium



SIDA: 4

WWW.KELBERG.SE | +46 070-536 3939 | 253 68, HELSINGBORG

Whilst every effort has been made to ensure that the information in this specification sheet is accurate, some errors may occur. It is important that you do not rely solely on this information, but that you check with your dealer any items that you believe will affect your decision to purchase this vehicle. Kel-Berg Trailers Sverige AB. accepts no responsibility for loss or damage resulting from incorrect or misleading information. This specification is for guidance only and does not constitute an offer of sale or warranty of the specification of this vehicle. All specifications are subject to change without notice and/or verification. E&OE.